

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Delphion


RESEARCH

INTEGRATED IAM

SERVICES

INSIDE DELPHION

The Delphion Integrated View


Buy Now:  PDF | [More choices...](#)Tools: Add to Work File: [Create new Work File](#) View: [INPADOC](#) | Jump to: [Top](#)  Go to: [Derwent...](#) [Email this to a friend](#)Title: **JP5074462A2: NONAQUEOUS ELECTROLYTE SECONDARY BATTERY**Country: **JP Japan**Kind: **A**Inventor: **NISHIKAWA YUKIO;
MORITA TERUYOSHI;**Assignee: **MATSUSHITA ELECTRIC IND CO LTD**
[News, Profiles, Stocks and More about this company](#)Published / Filed: **March 26, 1993 / Sept. 17, 1991**Application Number: **JP1991000236040**IPC Code: **H01M 4/64; H01M 4/02; H01M 10/40;**Priority Number: **Sept. 17, 1991 JP1991000236040**

Abstract:

PURPOSE: To provide a nonaqueous electrolyte secondary battery excellent in an overdischarge resistant characteristic and safety.

CONSTITUTION: In a nonaqueous electrolyte secondary battery which uses lithium-containing composite oxides of transition metals as positive electrode material and a carbonaceous material as negative electrode material, a negative electrode plate 2 which uses nickel, titanium, and stainless steel as core materials is heat treated at temperatures above 180°C. Thereby a very thin oxide film is formed on the surface of the core materials and so elusion of the core materials is prevented even if the electric potential of the negative electrode is raised by an overdischarging device, and thus the capacity of the battery is recovered simply by recharging. The ceiling temperature of the heat treatment is restricted depending on the thermal properties of the core materials and of a binding agent used.

COPYRIGHT: (C)1993,JPO&Japio

Family: [Show 9 known family members](#)Other Abstract Info: **CHEMABS 119(06)052972P CAN119(06)052972P DERABS C93-137911 DERC93-137911**[View Image](#)

1 page

[this for the Gallery...](#)**\$10 Off**
Handcrafted
Plaques
Order Today![Nominate](#)



(19)

(11) Publication number:

05074462 A

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **03236040**(51) Intl. Cl.: **H01M 4/64 H01M 4/02 H01M 10/40**(22) Application date: **17.09.91**

(30) Priority:	(71) Applicant: MATSUSHITA ELECTRIC IND CO LTD
(43) Date of application publication: 26.03.93	(72) Inventor: NISHIKAWA YUKIO MORITA TERUYOSHI
(84) Designated contracting states:	(74) Representative:

**(54) NONAQUEOUS
ELECTROLYTE
SECONDARY BATTERY**

(57) Abstract:

PURPOSE: To provide a nonaqueous electrolyte secondary battery excellent in an overdischarge resistant characteristic and safety.

CONSTITUTION: In a nonaqueous electrolyte secondary battery which uses lithium-containing composite oxides of transition metals as positive electrode material and a carbonaceous material as negative electrode material, a negative electrode plate 2 which uses nickel, titanium, and stainless steel as core materials is heat treated at temperatures above 180°C. Thereby a very thin oxide film is formed on the surface of the core materials and so elution of the core materials is prevented even if the electric potential of the negative electrode is raised by an overdischarging device, and thus the capacity of the battery is recovered simply by recharging. The ceiling temperature of the heat treatment is restricted depending on the thermal properties of the core

materials and of a binding agent used.

COPYRIGHT: (C)1993,JPO&Japio

